

MERCEDES-BENZ (EU) MARINE DIESEL ENGINES OM 312



ENGINE OM312 Capacity: 7-11 liter		
USE Normal		CLIMATE Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
<i>Change every 4500 km/ 100 hours</i>		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
<i>Change every 4500 km/ 100 hours</i>		
USE Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
<i>Change every 4500 km/ 100 hours</i>		
USE Initial service		CLIMATE Tropical
PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
<i>Change every 500 km/ 10 hours</i>		
USE Initial service		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
<i>Change every 500 km/ 10 hours</i>		
USE Initial service		CLIMATE Cold
PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
<i>Change every 500 km/ 10 hours</i>		



MERCEDES-BENZ (EU) MARINE DIESEL ENGINES OM 312



COOLING SYSTEM

Capacity: 11,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.